

**Tank :**

- ROUND-CROSS SECTION , WELDING BY ROBOT TECHNIQUE UNDER THE EUROPEAN STANDARDS
- Tanker is bottle type shape
- The chassis manufactured by high durable special alloy
- Chassis designed according to international standards under full load and various land situations. Overloading taken into consideration while durability calculations

**King Pin :**

King-Pin made of forged steel (42 Cr Mo 4) which is coherent to 2"SAE/DIN" norms and durable against high level stretching and breakings. It can be replaceable via screw connections

**Landing Gears :**

Landing Gears are double revolution and each has a capacity of bearing 25 tons

**Electrical System :**

According to EU regulations 24V electrical system used. On the semi-trailer there are multiple sectioned stop lamp which contains fog lamp, reverse gear lamp. 2 pieces plate lighten lamp, side lamps, indicators and reflectors. Front panel has two electrical sockets (24N/24S)

**Equipment :**

- According to EU standards tanker equipments
- DN500 Menhol covers, 3 " butterfly type discharge system

**Drain Pool :**

- On the right side of tanker anti-skid walkway
- Drainage piping for drain of rain water

**Axle, Suspension and Brake System :**

- Drum type axle
- Air suspension type suspension system
- According to European standards EBS brake system

**Standard Accessories :**

- Single spare Wheel place and spare wheel carrier
- 1 unit tool box
- 1 unit fireextinguisher box
- 1 unit plastic water tank
- 1 unit chock
- 6 unit mudguard ( for each tyre )
- 4 m discharge hose and storage box
- Traffic sign boards

**TYRE :**

385/65 R22,5 6+1 pcs

**RIM :**

11,75\*22,5 dimension ,steel 6+1 pcs

**Options**

- Capacity
- Clour and logo
- Pump
- Axle brand and type ( Turkish or German Brand , Drum or Disc )
- Type of rim ( Aluminium )
- Brake system ( EBS, ABS )
- Hand rail
- Equipments
- Heating system

**Paint :**

*The surfaces are cleaned under high pressure with water and bonder chemical liquid. Then it is dyed with one coat of epoxy die, and a last coat of acrylic die. It is very durable against chemical effectiveness. As desired, colours can be chosen from the RAL codes.*



**NURSAN GIDA OTOMOTİV NAKLİYAT SAN. ve TİC. LTD. ŞTİ.**

KONYA Organize Sanayi Bölgesi 20. Sk. No.14 Selçuklu / KONYA  
Tel : +90.332. 239 18 12 (Pbx) Fax : +90.332. 239 18 16

Selçuk V.D. : 632 007 6117 / Ticaret Sicil No: 27874

www.nursandorse.com  
info@nursantrailer.com

www.nursantrailer.com

Cover & Isolation: Cover sheet 1,2 mm galvanized coated, isolation material is 10 cm rock wool

2 PIECE MENHOL COVER: 40 CM ST 37

1 PIECE 3" ASPHALT VALVE

PAINT: yes

BURNER: ALARKO Mark or Baltur Mark, 2 pieces ALM 22 or BTL 22

HEATING PIPE: 6" 6mm or 8mm steel pipe, diesel tank

GENERATOR: 2 KW OR 3 KW GENERATOR(1 PIECE)

TEMPERATURE INDICATOR: 2 PIECES