



## NURSAN GIDA OTOMOTİV NAKLİYAT SAN. ve TİC. LTD. ŞTİ.

KONYA Organize Sanayi Bölgesi 20. Sk. No.14 Selçuklu / KONYA Tel: +90.332. 239 18 12 (Pbx) Fax: +90.332. 239 18 16

Selçuk V.D.: 632 007 6117 / Ticaret Sicil No: 27874

www.nursandorse.com info@nursantrailer.com www.nursantrailer.com

## **TANK CONSTRUCTION:**

Tank is "MILLENIUM" shape and discharging is from bottom. Tank is built with ST 37 thickness of 4mm. Working pressure 2 bar and test pressure 3.0 bar . 2 units , 450 mm diameter heavy duty screw type loading covers. 2 unit peneumatic air valve ,2 unit air pressure manometer . 4 " discharging system and 6 mt special alloy discharge hose and 2 unit regulated to 2.1 bar safety valve. Upper catwalk and Access ladder is set to trailer

# AIR COMPRESSOR :

Electric compressor

Axle:

3x12 tons drum brake

### **SUSPENSION SYTEM:**

Air suspension system

#### **BRAKE SYSTEM:**

EBS brake system

## LANDING GEAR:

Which are double revolution and each has a capacity of bearing 25 tons

TYRE:

385/65 R22,5 6+1 units.

RIM:

11,75\*22,5 dimension, steel

#### KING-PIN:

It is made of forged steel (42 Cr Mo 4) which is coherent to 2"SAE/DIN" norms and durable against high level stretching and breakings. It can be replaceable via screw connections.

# **ELECTRICAL SYSTEM:**

We have got 24 V electrical installment which is designed according to EU rules

There are stop lambs with many parts which consist of reverse light and fog light on the trailer. There are 2 electrical sockets (24N/24S) and an ABS socket on the front panel.





# NURSAN GIDA OTOMOTİV NAKLİYAT SAN. ve TİC. LTD. ŞTİ.

KONYA Organize Sanayi Bölgesi 20. Sk. No.14 Selçuklu / KONYA Tel: +90.332. 239 18 12 (Pbx) Fax: +90.332. 239 18 16

Selçuk V.D.: 632 007 6117 / Ticaret Sicil No: 27874

www.nursandorse.com info@nursantrailer.com www.nursantrailer.com

# **Standard Accessiories**

- 1 unit Single spare Wheel place
- 1 unit tool box
- -1 unit plastic water tank
- -1 unit chock
- 6 unit mudguard (for each tyre)
- -6 m discharge hose and storage box

# Options:

- Capacity
- Axle type ( disck , drum )
- Spring Type ( Z springs , leaf spring )
- Compressor type (electric, diesel)
- Rim type (steel, aluminium)
- Piece of loading manhole covers
- Piece of cone

## Paint:

The surfaces are cleaned under high pressure with water and bonder chemical liquid. Then it is dyed with one coat of epoxy die, and a last coat of acrylic die. It is very durable against chemical effectiveness. As desired, colours can be chosen from the RAL codes